

## ASCEND<sup>®</sup> 12" COMPOSITE BOARD & BATTEN **TECHNICAL SUMMARY**

PHYSICAL DATA					PRODUCT TEST DATA					
Panel Projection	3/4"				Impact Resis	stance	>35 inch lbs.			
Total Width Panel Exposure	13.6" 12"				Coefficient of Linear Expansion (in/in/°F) 2.3 x 10 <sup>-5</sup>					
					Thermal Resistance R-value 1.6					
Length	12 ft.				ASTM D 3345					
Weight	.62 lbs/ft.				Termite Resistance Complete Resistance					
Packaging	8 panels/carton (.96 square)				ASTM D 5206-13					
Color	Uniformity is spectrophotometrically controlled				Windload Resistance* 52 psf (12" OC nails) 65.3 psf (8" OC nails)					
Gloss	Uniform low		intained wit	h F	FIRE RESISTANCE					
	a 75° gloss meter				ASTM E84 - Class A					
Finish Cedar Mill or Matte					Flame Spread Index≤25Smoke Developed Index≤450					
					ASTM E119					
					Rated Assemblies Approved for Use					
					ASTM D635					
					Rate of Burn No Self Sustained Burn					
Cedar Mill Finish Matte Finish					ASTM D1929					
					Self Ignition Temp770°F (410°C)Flash Ignition Temp734°F (390°C)					
					NFPA 268					
					Section 1406 of IBC Approved for Use					
COLORS										
Glacier Almond White	Monterey Sand	Pebble	Canyon Drift	Flagship Brown	Rustic Timber	Dover Gray	Cape Cod Gray	Sterling Gray	Storm	
Ageless Charcoal Slate Smoke	Cast Iron	Laguna Blue	Harbor Blue	Midnight Blue	Riviera Dusk	Mountain Fern	Deep Moss	Fired Brick		

CODES AND REGULATORY COMPLIANCE

Intertek Code Compliance Research Report #0316 Florida Product Approval #46921 ICC-ES Evaluation Report - ESR 4449

## WARRANTY

ASCEND offers a Lifetime Limited Warranty<sup>\*\*</sup> to the original homeowner and is transferable if the home is sold.

**THREE PART FORMAT SPECIFICATION** Long form specification in three part format are

available on www.ASCENDCompositeCladding.com.

©2025 Associated Materials, LLC (AM) 3773 State Road, Cuyahoga Falls, Ohio 44223. Trademarks mentioned in this document are the property of AM, its affiliates, or their respective owners. \*Installation over 7/16" sheathing. Penetration into sheathing only. \*\*For a copy of the written product warranty, please visit www.ASCENDCompositeCladding.com or contact your ASCEND Sales Representative. Limited warranty does not apply to damage caused by faulty or improper installation, or causes outside of AM's control. Colors may be slightly different from their appearance in this sell sheet. Make final color selections using actual product samples. All specifications and designs subject to change without notice. 01/25 Digital 80-7333